

POLARIS BRUTUS BRUTUS HDPTO (2013-2014)



ENGINE Yanmar 3TNM72
Capacity: 2,3-2,6 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

DIFFERENTIAL FRONT
Capacity: 0,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

POWER TAKE OFF
Capacity: 0,18 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSMISSION CVT 1/1
Capacity: 1,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC SYSTEM
Capacity: 7,9 liter (Hydraulic system), Capacity: 2,61 liter (Reservoir)

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 2000 miles/ 24 months/ 200 hours

COOLING SYSTEM
Capacity: 5,9-6,7 liter

USE
Normal

CLIMATE
Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 11

Change every 2000 miles/ 24 months/ 200 hours

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.