

# QINGQI GY (ADVENTURE) QM 125 GY-2C

## (2008 AND AFTER)



### ENGINE/TRANSMISSION

Capacity: 0,8 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 4000 km/ 20 months*

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 3

**Expulsa RR 10W-40***Change every 4000 km/ 20 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

**Bi-Turbo 20W-50***Change every 1000 km/ 5 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

**Expulsa RR 5W-50**

PRODUCT RECOMMENDATION 2

**Expulsa RR 15W-50**

PRODUCT RECOMMENDATION 3

**Expulsa RR 10W-40***Change every 1000 km/ 5 months*

### BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

**Drauliquid-S DOT 4**

PRODUCT RECOMMENDATION 2

**Drauliquid DOT 3***Change every 4000 km/ 20 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.