ROYAL ENFIELD RUMBLER RUMBLER 500



(2014-2020)

| ENGINE/TRANSMISSION Capacity: 2,75 liter | | |
|---|-------------------------|----------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 15W-50 | | |
| Check every 1000 km/3 months, change e | every 6000 km/ 6 months | |
| USE | | CLIMATE |
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Expulsa RR 15W-50 | | |
| Change every 500 km/ 1 months | | |

| BRAKE SYSTEM Capacity: 60 CM3 (Front), Capacity: 10 | 00 CM3 (Rear) | |
|---|--------------------------|--------------------------|
| USE | | CLIMATE |
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | Drauliquid DOT 3 |

FRONT FORK

Capacity: 430 liter (each leg)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.