## **SUZUKI CP 50 CP 50 (ST)** (1989-1995)



ENGINE + AUTOMATIC LUBRICATION Capacity: 0,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Tornado	Scoosynth	Maestrol		

FINAL REDUCTION Capacity: 0,09 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

FRONT FORK Capacity: 0,05 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.