PRODUCT RECOMMENDATION

# SUZUKI DR(-Z) DR-Z 400 SM (2005 AND AFTER)

## ENGINE/TRANSMISSION
Capacity: 1,9 liter (Dry fill), Capacity: 1,8 liter (Service fill), Filter capacity: 0,1 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Bi-Turbo 20W-50** | | |

*Change every 6000 km/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Expulsa RR 5W-50** | **Expulsa RR 15W-50** | **Expulsa RR 5W-40** |

*Change every 6000 km/ 6 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Mediterranean |
| PRODUCT RECOMMENDATION 1 | | |
| **Bi-Turbo 20W-50** | | |

*Change every 1000 km/ 1 months*

| USE | | CLIMATE |
|---|---|---|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| **Expulsa RR 5W-50** | **Expulsa RR 15W-50** | **Expulsa RR 5W-40** |

*Change every 1000 km/ 1 months*

## HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| **Drauliquid-LV Super DOT 4** | **Drauliquid-S DOT 4** | |

*Check every 6000 km/ 6 months, change every 24 months*

## COOLING SYSTEM
Capacity: 1,25 liter

| USE | | CLIMATE |
|---|---|---|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| **Coolant -38 Organic NF** | | |

*Change every 24 months*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367

PRODUCT RECOMMENDATION

# SUZUKI DR(-Z) DR-Z 400 SM (2005 AND AFTER)

**FRONT FORK**
Capacity: 182 CM3 (Inner tube), Capacity: 350 CM3 (Outer tube)

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367