SUZUKI LT LT-A 400/F KINGQUAD (2010 AND AFTER)



ENGINE Capacity: 3,4 liter (Dry fill), Capacity: 3,1 liter (Service fill), Filter capacity: 0,2 liter					
use Normal		climate Moderate			
				PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Expulsa RR 5W-40	Expulsa RR 10W-40	Expulsa 10W-40			
Change every 2000 km/ 6 months					
USE		CLIMATE			
Initial service		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Expulsa RR 5W-40	Expulsa RR 10W-40	Expulsa 10W-40			
Change avery 200 km/1 months	1	1			

Change every 200 km/ 1 months

CLIMATE
Moderate
ENDATION 2
L-3/GL-5 80W-90

Check every 2000 km/ 6 months, change every 24 months

GEARBOX HIGH/LOW 2/1 Capacity: 0,35 liter			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90		

Check every 2000 km/ 6 months, change every 24 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and ma	x.)		
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 1000 km/ 3 months, change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.