

SUZUKI RM(-Z) RM 80 (1996-2001)**ENGINE**

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Tornado	Scoosynth	Maestrol

TRANSMISSION 6

Capacity: 0,55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40

HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Change every 12 months***COOLING SYSTEM**

Capacity: 0,55 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

*Change every 12 months***FRONT FORK**

Capacity: 0,36 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

SUZUKI RM(-Z) RM 80 (1996-2001)**SHOCK ABSORBER REAR**

Capacity: 0,15 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Fork Oil RR 10		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.