SUZUKI M109R / VZR INTRUDER/ BOULEVARD M109R / VZR1800 / M1800Z INTRUDER K7/K8/K9 (2007-2010)



ENGINE/TRANSMISSION Capacity: 3,6 liter, Capacity: 4,7 liter (Overhaul capacity), Filter capacity: 0,2 liter					
use Normal		climate Moderate			
				PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40			
Change every 6000 km/ 12 months	5				
USE		CLIMATE			
Initial service		Moderate			
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3			
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 5W-40			

Change every 1000 km/2 months

SHAFT DRIVE Capacity: 0,2 liter, Capacity: 0,22 liter (Overhaul capacity)				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Check every 12000 km/ 24 months				
USE		CLIMATE		
Normal		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	SP Gear 1071			
Check every 12000 km/ 24 months				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90			
Change every 1000 km/ 2 months				
USE		CLIMATE		
Initial service		Arctic		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	SP Gear 1071			
Change every 1000 km/ 2 months				

SUZUKI M109R / VZR INTRUDER/ BOULEVARD M109R / VZR1800 / M1800Z INTRUDER K7/K8/K9 (2007-2010)



HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 6000 km/ 12 months, change every 24 months

COOLING SYSTEM Capacity: 2,7 liter			
USE	CLIMATE		
Normal	Moderat	e	
PRODUCT RECOMMENDATION 1			
Coolant -38 Organic NF			
Check every 6000 km/ 12 months, change every 24 months			

FRONT FORK

Capacity: 0,7 liter (each side)

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.