PRODUCT RECOMMENDATION

SYM ALLO ALLO 50 (2010-2017)

ENGINE
Capacity: 0,8 liter (Dry fill), Capacity: 0,75 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	**Expulsa 10W-40**	

Check every 1000 km/ 1 months, change every 3000 km/ 3 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	**Expulsa 10W-40**	

Change every 300 km

FINAL GEAR
Capacity: 100 CM3 (Dry fill), Capacity: 90 CM3 (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 5000 km/ 5 months

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Gearlube GL-4 80W-90	**Unigear HS GL-3/GL-5 80W-90**	

Change every 300 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367