SYM HD EVO LH HD EVO 125 LH12W (2004-2011)



ENGINE Capacity: 1 liter (Dry fill), Capacity: 0,8 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Expulsa RR 10W-40	Expulsa 10W-40			
Change every 3000 km				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Expulsa RR 10W-40	Expulsa 10W-40			

Change every 300 km

FINAL GEAR Capacity: 0,11 liter (Dry fill), Capacity: 0,1 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Gearlube GL-5 85W-140				
Change every 5000 km/ 5 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1				

Gearlube GL-5 85W-140

Change every 300 km

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid DOT 3	

SYM HD EVO LH HD EVO 125 LH12W (2004-2011)



COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Coolant -38 Organic NF	Coolant -26			
01 10 11				

Change every 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.