TANK SPORTS LB50QT-16 LB50QT-16



ENGINE Capacity: 0-0 liter (Between min and a	max.)	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	
Change every 1000 km		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Expulsa RR 10W-40	Expulsa 10W-40	
Change every 300 km		

HUB REDUCTIONS REAR Capacity: 0,11 liter		
JSE		CLIMATE
Normal		Moderate
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90
Change every 3000 km		
SE		CLIMATE
nitial service		Moderate
RODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Gearlube HS GL-5 75W-90	Syngear 75W-90

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.