

# WK BIKES JETMAX JETMAX 250I CF250T-6A

## (2010-2016)

**ENGINE**

Capacity: 1,5 liter (Dry fill), Capacity: 1,45 liter (Service fill), Filter capacity: 0,05 liter

## USE

Normal

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 2000 km*

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

## PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 2000 km*

## USE

Initial service

## CLIMATE

Mediterranean

## PRODUCT RECOMMENDATION 1

**Expulsa RR 15W-50**

## PRODUCT RECOMMENDATION 2

**Bi-Turbo 20W-50***Change every 1000 km*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40**

## PRODUCT RECOMMENDATION 2

**Expulsa 10W-40***Change every 1000 km***HUB REDUCTIONS REAR**

Capacity: 0,3 liter

## USE

Normal

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 10000 km*

## USE

Initial service

## CLIMATE

Moderate

## PRODUCT RECOMMENDATION 1

**Expulsa RR 10W-40***Change every 2000 km*

# WK BIKES JETMAX JETMAX 250I CF250T-6A (2010-2016)



## HYDRAULIC BRAKE SYSTEM

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
<b>Drauliquid-LV Super DOT 4</b>	<b>Drauliquid-S DOT 4</b>	<b>Drauliquid DOT 3</b>

## COOLING SYSTEM

Capacity: 2,1 liter (Radiator + engine), Capacity: 0,3 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
<b>Coolant -38 Organic NF</b>	<b>Coolant -26</b>	

*Change every 24 months*

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*