

YAMAHA SNOWMOBILES FX NYTRO FX NYTRO FX10 (2008-2009)

**ENGINE**

Capacity: 3,9 liter (Dry fill), Capacity: 3,2 liter (Service fill), Filter capacity: 0,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Drauliquid-LV Super DOT 4****PRODUCT RECOMMENDATION 2****Drauliquid-S DOT 4***Change every 24 months***COOLING SYSTEM**

Capacity: 3,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**Coolant -38 Organic NF****CHAINCASE**

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1**SP Gear 1081****PRODUCT RECOMMENDATION 2****SP Gear 5015****PRODUCT RECOMMENDATION 3****Gearlube GL-4 80W***Change every 2500 miles/ 200 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.