

# YAMAHA SNOWMOBILES FX NYTRO FX NYTRO XTX FX10XT (2009-2010)

**ENGINE**

Capacity: 3,9 liter (Dry fill), Capacity: 3,2 liter (Service fill), Filter capacity: 0,2 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

**HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE                              |                           | CLIMATE  |
|----------------------------------|---------------------------|----------|
| Normal                           |                           | Moderate |
| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |          |
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |          |

*Change every 24 months***COOLING SYSTEM**

Capacity: 3,4 liter

| USE                           |  | CLIMATE  |
|-------------------------------|--|----------|
| Normal                        |  | Moderate |
| PRODUCT RECOMMENDATION 1      |  |          |
| <b>Coolant -38 Organic NF</b> |  |          |

**CHAINCASE**

Capacity: 0,2 liter

| USE                      |                          | CLIMATE  |
|--------------------------|--------------------------|----------|
| Normal                   |                          | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |          |
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |          |

*Change every 2500 miles/ 200 hours/ 12 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.