

YAMAHA (USA) WR WR 250 R (2010-2015)**ENGINE/TRANSMISSION**

Capacity: 1,4 liter (Dry fill), Capacity: 1,1 liter (Service fill), Filter capacity: 0,1 liter

USE		CLIMATE
Normal		Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

Change every 4000 miles/ 6 months

USE		CLIMATE
Initial service		Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 5W-50	Expulsa RR 15W-50	Expulsa RR 10W-40

*Change every 600 miles/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

*Check every 4000 miles/ 6 months, change every 24 months***COOLING SYSTEM**

Capacity: 0,9 liter

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 13000 miles/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.