

YAMAHA (USA) XV ROAD STAR XV 17

ROAD STAR (2004-2008)

**ENGINE/TRANSMISSION**

Capacity: 4,1 liter, Filter capacity: 0,4 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 4000 miles/ 6 months*

USE	CLIMATE
Initial service	Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 600 miles/ 1 months***FINAL DRIVES**

Capacity: 0,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Check every 8000 miles/ 12 months, change every 16000 miles/ 24 months*

USE	CLIMATE
Initial service	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Change every 600 miles/ 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.