

# YAMAHA (USA) XVS V-STAR XVS 65 V STAR CLASSIC (2010-2010)



## ENGINE/TRANSMISSION

Capacity: 2,8 liter (Service fill), Filter capacity: 0,2 liter

| USE    | CLIMATE       |
|--------|---------------|
| Normal | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> |

*Change every 4000 miles/ 6 months*

| USE             | CLIMATE       |
|-----------------|---------------|
| Initial service | Mediterranean |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
|--------------------------|--------------------------|--------------------------|
| <b>Expulsa RR 5W-50</b>  | <b>Expulsa RR 15W-50</b> | <b>Expulsa RR 10W-40</b> |

*Change every 600 miles/ 1 months*

## FINAL DRIVES

Capacity: 0,2 liter

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |  |

*Check every 4000 miles/ 6 months, change every 16000 miles/ 24 months*

| USE             | CLIMATE  |
|-----------------|----------|
| Initial service | Moderate |

| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 |  |
|--------------------------|--------------------------|--|
| <b>SP Gear 5015</b>      | <b>Gearlube GL-4 80W</b> |  |

*Change every 600 miles/ 1 months*

## HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

| PRODUCT RECOMMENDATION 1         | PRODUCT RECOMMENDATION 2  |  |
|----------------------------------|---------------------------|--|
| <b>Drauliquid-LV Super DOT 4</b> | <b>Drauliquid-S DOT 4</b> |  |

*Check every 4000 miles/ 6 months, change every 24 months*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.