

PRODUCT RECOMMENDATION

YAMAHA (USA) YFM GRIZZLY YFM 45 GRIZZLY 450 4X4 EPS YFM45FGP/FGPH (2011-2014)



ENGINE

Capacity: 2,4 liter, Filter capacity: 0,1 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 3

Expulsa 10W-40

Change every 1600 miles/ 6 months/ 160 hours

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40

Change every 1600 miles/ 6 months/ 160 hours

USE

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa RR 15W-50

PRODUCT RECOMMENDATION 2

Expulsa RR 10W-40

PRODUCT RECOMMENDATION 3

Expulsa 10W-40

Change every 200 miles/ 1 months/ 20 hours

USE

Initial service

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40

Change every 200 miles/ 1 months/ 20 hours

DIFFERENTIAL REAR

Capacity: 0,23 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

FINAL GEAR

Capacity: 0,38 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 24 months

PRODUCT RECOMMENDATION

YAMAHA (USA) YFM GRIZZLY YFM 45 GRIZZLY 450 4X4 EPS YFM45FGP/FGPH (2011-2014)



COOLING SYSTEM

Capacity: 1,3 liter (Radiator), Capacity: 0,25 liter (Reservoir)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.