

YAMAHA (USA) YFM GRIZZLY YFM 66 FP GRIZZLY (2005-2008)

**ENGINE**

Capacity: 2 liter, Filter capacity: 0,1 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 1600 miles/ 6 months/ 160 hours*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1600 miles/ 6 months/ 160 hours*

USE

First change only

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 200 miles/ 1 months/ 20 hours*

USE

First change only

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 200 miles/ 1 months/ 20 hours***DIFFERENTIAL REAR**

Capacity: 0,28 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Change every 3200 miles/ 12 months/ 320 hours*

USE

First change only

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Change every 200 miles/ 1 months/ 20 hours*

YAMAHA (USA) YFM GRIZZLY YFM 66 FP GRIZZLY (2005-2008)



HUB REDUCTIONS REAR

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 3200 miles/ 12 months/ 320 hours

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 200 miles/ 1 months/ 20 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

COOLING SYSTEM

Capacity: 0,78 liter (Radiator), Capacity: 0,29 liter (Reservoir), Capacity: 1,8 liter (Total)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.