

YAMAHA (USA) YFM KODIAK YFM 40

KODIAK 4X4 (2005-2007)

**ENGINE**

Capacity: 2,6 liter (Dry fill), Capacity: 2,4 liter (Service fill), Filter capacity: 0,1 liter

USE

Normal

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 6 months*

USE

Normal

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 6 months*

USE

Initial service

CLIMATE

Mediterranean

PRODUCT RECOMMENDATION 1

Expulsa 10W-40*Change every 1 months*

USE

Initial service

CLIMATE

Arctic

PRODUCT RECOMMENDATION 1

Expulsa RR 5W-40*Change every 1 months***DIFFERENTIAL**

Capacity: 0,35 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Change every 12 months*

USE

Initial service

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

Gearlube GL-4 80W*Change every 1 months*

YAMAHA (USA) YFM KODIAK YFM 40 KODIAK 4X4 (2005-2007)

**FINAL GEAR**

Capacity: 0,16 liter

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 5015 | Gearlube GL-4 80W | |

Change every 12 months

| USE | | CLIMATE |
|--------------------------|--------------------------|----------|
| Initial service | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| SP Gear 5015 | Gearlube GL-4 80W | |

*Change every 1 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE | | CLIMATE |
|----------------------------------|---------------------------|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | |

*Change every 24 months***COOLING SYSTEM**

Capacity: 1,1 liter

| USE | | CLIMATE |
|-------------------------------|--|----------|
| Normal | | Moderate |
| PRODUCT RECOMMENDATION 1 | | |
| Coolant -38 Organic NF | | |

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.