YAMAHA (USA) YFM RAPTOR YFM 80 RAPTOR (2002-2005)



ENGINE/TRANSMISSION Capacity: 0,95 liter (Dry fill), Capacity: 0,8 liter (Service fill)			
USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1			
Expulsa 10W-40			
Change every 6 months			
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1			
Expulsa 10W-40			
Change every 1 months			

FINAL DRIVES Capacity: 0,12 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 12 months		
USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
		1

Change every 1 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.