PRODUCT RECOMMENDATION

YAMAHA (USA) YZF-R6 YZF-R6 (2008-2009)



ENGINE/TRANSMISSION Capacity: 2,6 liter (Service fill), Filter capacity: 0,2 liter			
use Normal		сциате Mediterranean	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	
Change every 4000 miles/ 6 month	S		
USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3	
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40	
O I O OO I I I I I I I I	1	1	

Change every 600 miles/ 1 months

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Change every 24 months

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		
Change every 16000 miles/ 24 months	·	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.