YAMAHA FZ6 FAZER FZ6-NS FAZER 1B35



(2005-2005)

ENGINE/TRANSMISSION Capacity: 2,8 liter, Capacity: 3,4 liter (Overhaul capacity), Filter capacity: 0,3 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40		
Chack every 2000 km, change every 10000 km/12 months				

Check every 3000 km, change every 10000 km/ 12 months

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Change every 1000 km

HYDRAULIC BRAKE SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 10000 km/12 months, change every 24 months

COOLING SYSTEM Capacity: 0,6 liter (Radiator), Capacity: 0,27 liter (Reservoir), Capacity: 2 liter (Total)			
USE	CLIMATE		
Normal	Moderate		
PRODUCT RECOMMENDATION 1			
Coolant -38 Organic NF			

Check every 10000 km/ 12 months, change every 36 months

FRONT FORK Capacity: 0,47 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Fork Oil RR 10	
Check every 10000 km/ 12 months	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the

information contained herein is subject to changes without notification.