YAMAHA XJ DIVERSION XJ 900 S DIVERSION 4KMD (2002-2004)



| ENGINE/TRANSMISSION Capacity: 3,4 liter, Capacity: 4,4 liter (Total), Filter capacity: 0,2 liter | | | | |
|--|--------------------------|--------------------------|--|--|
| USE | | CLIMATE | | |
| Normal | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Expulsa RR 15W-50 | Expulsa RR 10W-40 | Expulsa 10W-40 | | |
| Check every 3000 km, change every 10000 km/ 12 months | | | | |
| USE | | CLIMATE | | |
| Initial service | | Mediterranean | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 | | |
| Expulsa RR 15W-50 | Expulsa RR 10W-40 | Expulsa 10W-40 | | |

| SHAFT DRIVE Capacity: 0,2 liter | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| SP Gear 5015 | Gearlube GL-4 80W | | | |
| Check every 10000 km, change every 20000 km | | | | |
| USE | | CLIMATE | | |
| Initial service | | Moderate | | |

| 01 | | | | |
|--------------------------|--------------------------|----------|--|--|
| SP Gear 5015 | Gearlube GL-4 80W | | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Initial service | | Moderate | | |
| USE | | CLIMATE | | |

Change every 1000 km

Change every 1000 km

| HYDRAULIC BRAKE SYSTEM | | | | |
|---|--------------------------|----------|--|--|
| USE | | CLIMATE | | |
| Normal | | Moderate | | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | | |
| Check every 10000 km/ 12 months, change every 24 months | | | | |

YAMAHA XJ DIVERSION XJ 900 S DIVERSION 4KMD (2002-2004)



| FRONT FORK Capacity: 0,44 liter | |
|---------------------------------|----------|
| USE | CLIMATE |
| Normal | Moderate |
| PRODUCT RECOMMENDATION 1 | |
| Fork Oil RR 10 | |
| Check every 10000 km | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.