## YAMAHA XP TMAX XP 500 TMAX 5VU1

(2004-2004)



ENGINE Capacity: 2,9 liter, Capacity: 3,6 liter (Total), Filter capacity: 0,1 liter				
USE		CLIMATE		
Normal		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		
Change every 5000 km				
USE		CLIMATE		
Initial service		Mediterranean		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3		
Expulsa RR 10W-40	Expulsa 10W-40	HDX 10W-40		
Change every 1000 km				

SHAFT DRIVE Capacity: 0,65 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Change every 10000 km/ 12 month	, IS	,

HYDRAULIC BRAKE SYSTEM			
USE		CLIMATE	
Normal		Moderate	
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2		
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		

Check every 10000 km/ 12 months, change every 24 months

COOLING SYSTEM Capacity: 0,25 liter (Reservoir), Capacity: 1,5 liter (Total)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1				
Coolant -38 Organic NF				
Check every 10000 km/ 12 months, change every 36 months				

## YAMAHA XP TMAX XP 500 TMAX 5VU1

(2004-2004)



FRONT FORK Capacity: 0,51 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Perlus H 32	
Check every 10000 km	

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.