YAMAHA YFM GRIZZLY YFM GRIZZLY 80

(2006-2008)



ENGINE/TRANSMISSION Capacity: 0,8 liter		
USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 6 months		
USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 6 months		
USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 1 months		
USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Evalua DD EW 40	I .	I
Expulsa RR 5W-40		
Change every 1 months		
Change every 1 months HUB REDUCTIONS REAR		CLIMATE
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter		climate Moderate
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE	PRODUCT RECOMMENDATION 2	
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE Normal	PRODUCT RECOMMENDATION 2 Gearlube GL-4 80W	
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE Normal PRODUCT RECOMMENDATION 1		
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE Normal PRODUCT RECOMMENDATION 1 SP Gear 5015		
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter use Normal PRODUCT RECOMMENDATION 1 SP Gear 5015 Change every 12 months		Moderate
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE Normal PRODUCT RECOMMENDATION 1 SP Gear 5015 Change every 12 months USE		Moderate
Change every 1 months HUB REDUCTIONS REAR Capacity: 0,12 liter USE Normal PRODUCT RECOMMENDATION 1 SP Gear 5015 Change every 12 months USE Initial service	Gearlube GL-4 80W	Moderate

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.