YAMAHA YFM KODIAK YFM 400 KODIAK 4X4 (2000-2003)



JSE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 6 months		
JSE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 6 months		
JSE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1		
Expulsa 10W-40		
Change every 1 months		
JSE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		
Change every 1 months		
DIFFERENTIAL	0.07 11 (0.11 (11)	
Capacity: 0,42 liter (Dry fill), Capacit	y: 0,35 liter (Service fill)	
use Normal		CLIMATE Moderate
		Moderate
PRODUCT RECOMMENDATION 1 SP Gear 5015	PRODUCT RECOMMENDATION 2 Gearlube GL-4 80W	
	Geanube GL-4 6000	
Change every 12 months		
JSE		CLIMATE
initial complete		Moderate
nitial service	PRODUCT RECOMMENDATION 2	

YAMAHA YFM KODIAK YFM 400 KODIAK 4X4 (2000-2003)



FINAL GEAR Capacity: 0,22 liter (Dry fill), Capacity: 0,19 liter (Service fill)				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	Gearlube GL-4 80W			
Change every 12 months				
USE		CLIMATE		
Initial service		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
SP Gear 5015	Gearlube GL-4 80W			
Change every 1 months				

HYDRAULIC BRAKE SYSTEM Capacity: 0-0 liter (Between min and max.)			
use Normal		сымате Moderate	
			PRODUCT RECOMMENDATION 1
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4		
Change every 24 months		'	

COOLING SYSTEM Capacity: 0-0 liter (Between min and max.)		
USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.