YAMAHA YP X-MAX YP 250I R X-MAX (2008-2009)

ENGINE
Capacity: 1,2 liter

USE		CLIMATE	
Normal		Mediterranean	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Expulsa RR 15W-50	**Expulsa RR 10W-40**	**Expulsa 10W-40**	

Change every 3000 km

USE		CLIMATE	
Initial service		Mediterranean	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**	
Expulsa RR 15W-50	**Expulsa RR 10W-40**	**Expulsa 10W-40**	

Change every 1000 km

HUB REDUCTIONS REAR
Capacity: 0,25 liter

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Expulsa RR 10W-40	**HDX 10W-40**	

Change every 20000 km

USE	CLIMATE	
Initial service	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Expulsa RR 10W-40	**HDX 10W-40**	

Change every 1000 km

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE	CLIMATE	
Normal	Moderate	
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	

Change every 24 months

YAMAHA YP X-MAX YP 250I R X-MAX (2008-2009)

COOLING SYSTEM
Capacity: 1,4 liter (Radiator), Capacity: 0,26 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 36 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.