

YAMAHA YXR RHINO YXR 700 RHINO (2008-2009)

**ENGINE**

Capacity: 2,1 liter, Filter capacity: 0,1 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Change every 2400 km/ 6 months/ 150 hours

USE		CLIMATE
Normal		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

Change every 2400 km/ 6 months/ 150 hours

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Change every 320 km/ 1 months/ 20 hours

USE		CLIMATE
Initial service		Arctic
PRODUCT RECOMMENDATION 1		
Expulsa RR 5W-40		

*Change every 320 km/ 1 months/ 20 hours***DIFFERENTIAL**

Capacity: 0,18 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 4800 km/ 12 months/ 300 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 320 km/ 1 months/ 20 hours

YAMAHA YXR RHINO YXR 700 RHINO (2008-2009)



FINAL GEAR

Capacity: 0,25 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 4800 km/ 12 months/ 300 hours

USE		CLIMATE
Initial service		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	

Change every 320 km/ 1 months/ 20 hours

HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 24 months

COOLING SYSTEM

Capacity: 2,35 liter (Radiator), Capacity: 0,32 liter (Reservoir)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant -38 Organic NF		

Change every 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.