PRODUCT RECOMMENDATION

ZNEN ZN50QT ZN50QT-15E B OWL

ENGINE BN139QMB
Capacity: 0,9 liter

USE		CLIMATE
Normal		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Expulsa RR 15W-50	**Expulsa RR 10W-40**	**Expulsa 10W-40**
Change every 2500 km/ 6 months		

USE		CLIMATE
Initial service		Mediterranean
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Expulsa RR 15W-50	**Expulsa RR 10W-40**	**Expulsa 10W-40**
Change every 300 km/ 1 months		

FINAL REDUCTION
Capacity: 110 CM3

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	**PRODUCT RECOMMENDATION 3**
Gearlube GL-4 80W-90	**Gearlube GL-5 80W-90**	**Unigear HS GL-3/GL-5 80W-90**
Change every 5000 km/ 12 months		

HYDRAULIC BRAKE SYSTEM
Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	**PRODUCT RECOMMENDATION 2**	
Drauliquid-LV Super DOT 4	**Drauliquid-S DOT 4**	
Change every 5000 km/ 12 months		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.

KROON-OIL B.V.
Postbus 149
7600 AC Almelo

Dollegoorweg 15
7602 EC Almelo

Telefoon 0546-818165
Verkoop 0546-816184

Telefax 0546-817367