

ZNEN ZN50QT ZN50QT-8D E FALCON5**ENGINE BN139QMB**

Capacity: 0,9 liter

USE		CLIMATE
Normal		Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

Change every 2500 km/ 6 months

USE		CLIMATE
Initial service		Mediterranean

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Expulsa RR 15W-50	Expulsa RR 10W-40	Expulsa 10W-40

*Change every 300 km/ 1 months***FINAL REDUCTION**

Capacity: 110 CM3

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Gearlube GL-4 80W-90	Gearlube GL-5 80W-90	Unigear HS GL-3/GL-5 80W-90

*Change every 5000 km/ 12 months***HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 5000 km/ 12 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.