ZONTES MONSTER MONSTER 125 ZT125-5A (2013-2017)



| Expulsa RR 5W-50 | Expulsa RR 15W-50 | Expulsa RR 10W-40 |
|--------------------------------|--------------------------|--------------------------|
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| nitial service | | Moderate |
| SE | | CLIMATE |
| Change every 1000 km/ 5 months | | |
| Bi-Turbo 20W-50 | | |
| RODUCT RECOMMENDATION 1 | | |
| nitial service | | Mediterranean |
| SE | | CLIMATE |
| Change every 3000 km/20 months | 3 | |
| Expulsa RR 5W-50 | Expulsa RR 15W-50 | Expulsa RR 10W-40 |
| RODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | PRODUCT RECOMMENDATION 3 |
| Normal | | Moderate |
| SE | | CLIMATE |
| Change every 3000 km/20 months | 3 | |
| Bi-Turbo 20W-50 | | |
| RODUCT RECOMMENDATION 1 | | |
| Vormal | | Mediterranean |
| SE | | CLIMATE |

| HYDRAULIC BRAKE SYSTEM | | | |
|---------------------------|--------------------------|----------|--|
| USE | | CLIMATE | |
| Normal | | Moderate | |
| PRODUCT RECOMMENDATION 1 | PRODUCT RECOMMENDATION 2 | | |
| Drauliquid-LV Super DOT 4 | Drauliquid-S DOT 4 | | |
| | - | · | |

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.