

PRODUCT RECOMMENDATION

ACURA (USA / CAN) INTEGRA INTEGRA 1.8 (125 KW) (USA) (1996-2001)



ENGINE F18C

Capacity: 4,6 liter (Dry fill), Capacity: 3,8 liter (Service fill), Filter capacity: 0,3 liter

USE	CLIMATE
Normal	Mediterranean

PRODUCT RECOMMENDATION 1

Emperol 10W-40

Change every 12000 km/ 12 months

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 12000 km/ 12 months

USE	CLIMATE
Severe	Mediterranean

PRODUCT RECOMMENDATION 1

Emperol 10W-40

Change every 6000 km/ 6 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

Asyntho 5W-30

Change every 6000 km/ 6 months

ACURA (USA / CAN) INTEGRA INTEGRA 1.8 (125 KW) (USA) (1996-2001)

**TRANSAXLE AUTOMATIC 4/1**

Capacity: 5,9 liter (Dry fill), Capacity: 2,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 96000 km/ 60 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 48000 km/ 24 months*

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 192000 km/ 120 months*

USE	CLIMATE
First change only, severe	Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026*Change every 96000 km/ 36 months***TRANSAXLE MANUAL 5/1**

Capacity: 2,2-2,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 192000 km/ 72 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 60000 km/ 36 months*

ACURA (USA / CAN) INTEGRA INTEGRA 1.8 (125 KW) (USA) (1996-2001)



HYDRAULIC BRAKE SYSTEM

Capacity: 0-0 liter (Between min and max.)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	Drauliquid DOT 3

Change every 36 months

POWER STEERING

Capacity: 0-0 liter (Between min and max.)

We are unable to give a standard recommendation for this component. Please contact our service department.

COOLING SYSTEM

Capacity: 6,4-6,7 liter (Initial fill), Capacity: 4,4-4,7 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 192000 km/ 120 months

USE		CLIMATE
First change only		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Change every 96000 km/ 60 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.