

# ACURA (USA / CAN) RDX TB3/4 RDX 3.5 I-VTEC V6 (2015-2018)

**ENGINE J35Z6**

Capacity: 4,3 liter (Service fill), Filter capacity: 0,3 liter

| USE            | CLIMATE  |
|----------------|----------|
| Flexible (max) | Moderate |

PRODUCT RECOMMENDATION 1

**Presteza MSP 0W-20***Change every 12 months***TRANSAXLE AUTOMATIC 6/1**

Capacity: 3,1 liter

| USE                       | CLIMATE  |
|---------------------------|----------|
| Severe, first change only | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Change every 30000 miles*

| USE    | CLIMATE  |
|--------|----------|
| Severe | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036***Change every 60000 miles*

| USE                                    | CLIMATE  |
|--|----------|
| Flexible (on board maintenance system) | Moderate |

PRODUCT RECOMMENDATION 1

**SP Matic 4036****HYDRAULIC BRAKE SYSTEM**

Capacity: 0-0 liter (Between min and max.)

| USE    | CLIMATE  |
|--------|----------|
| Normal | Moderate |

PRODUCT RECOMMENDATION 1

**Drauliquid DOT 3***Change every 36 months*

# ACURA (USA / CAN) RDX TB3/4 RDX 3.5 I-VTEC V6 (2015-2018)



## COOLING SYSTEM

Capacity: 7,4 liter (Service fill)

| USE                                    |  | CLIMATE  |
|--|--|----------|
| Flexible (on board maintenance system) |  | Moderate |
| PRODUCT RECOMMENDATION 1               |  |          |
| Coolant SP 14+                         |  |          |

## AIRCONDITIONING COMPRESSOR

Capacity: 70-82 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

## AIRCONDITIONING SYSTEM

Capacity: 430-480 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

*The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.*