

ACURA (USA / CAN) RSX DC5 RSX BASE (USA) (2002-2006)

**ENGINE K20A3**

Capacity: 5,3 liter (Dry fill), Capacity: 4,2 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

Change every 16000 km/ 12 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2
Presteza MSP 5W-30	Armado Synth LSP Ultra 5W-30

*Change every 8000 km/ 6 months***TRANSAXLE AUTOMATIC 5/1**

Capacity: 6,5 liter (Dry fill), Capacity: 2,7 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 144000 km/ 60 months

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 48000 km/ 24 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 192000 km/ 120 months

USE	CLIMATE
First change only, severe	Moderate

PRODUCT RECOMMENDATION 1	
SP Matic 4026	

Change every 96000 km/ 36 months

ACURA (USA / CAN) RSX DC5 RSX BASE (USA) (2002-2006)



TRANSAXLE MANUAL 5/1

Capacity: 1,7 liter (Dry fill), Capacity: 1,5 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 192000 km/ 72 months*

USE	CLIMATE
Severe	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015*Change every 96000 km/ 36 months*

HYDRAULIC BRAKE SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 1 months, change every 36 months*

HYDRAULIC CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

PRODUCT RECOMMENDATION 3

Drauliquid DOT 3*Check every 1 months, change every 36 months*

POWER STEERING

We are unable to give a standard recommendation for this component. Please contact our service department.

ACURA (USA / CAN) RSX DC5 RSX BASE (USA) (2002-2006)



COOLING SYSTEM

Capacity: 6,4 liter (Dry fill), Capacity: 5,1 liter (Service fill)

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Change every 96000 km/ 60 months

USE	CLIMATE
First change only	Moderate

PRODUCT RECOMMENDATION 1

Coolant SP 14+

Change every 192000 km/ 120 months

AIRCONDITIONING COMPRESSOR

We are unable to give a standard recommendation for this component. Please contact our service department.

AIRCONDITIONING SYSTEM

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.