

ACURA (USA / CAN) TL UA8, UA9 TL 3.7 SH-AWD (2012-2014)

**ENGINE J37A4**

Capacity: 5 liter (Dry fill), Capacity: 4,3 liter (Service fill)

USE

Flexible (on board maintenance system)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Duranza ECO 5W-20**DIFFERENTIAL REAR**

Capacity: 2,5-2,8 liter

We are unable to give a standard recommendation for this component. Please contact our service department.

TRANSAXLE AUTOMATIC 6/1

Capacity: 3,1 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4036**TRANSAXLE MANUAL 6/1**

Capacity: 2,5 liter (Initial fill), Capacity: 2,1 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015**TRANSFERBOX**

Capacity: 0,4-0,5 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Gearlube GL-4 80W-90

PRODUCT RECOMMENDATION 2

Gearlube GL-5 80W-90**HYDRAULIC BRAKE SYSTEM****USE**

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid DOT 3

ACURA (USA / CAN) TL UA8, UA9 TL 3.7 SH-AWD (2012-2014)

**COOLING SYSTEM**

Capacity: 8,3 liter (Dry fill), Capacity: 6,3 liter (Service fill)

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.