

ALFA ROMEO (EU) 159 939 159 2.0 JTDM 16V (125 KW) (2009-2011)



MOTOR 939B3000

Kapacitet: 4,9 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Presteza MSP 5W-30

PRODUKTANBEFALING 2

Avanza MSP+ 5W-30

PRODUKTANBEFALING 3

Avanza RPC 5W-30

Kontroller alle 3000 km, skift alle 30000 km/ 24 måneder

TRANSAKSEL MANUEL 6/1

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Drauliquid-LV Super DOT 4

PRODUKTANBEFALING 2

Drauliquid-S DOT 4

Skift alle 30000 km/ 24 måneder

SERVOSTYRING

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Fluid 3013

Kontroller alle 24 måneder/ 30000 km

SMØREPUNKTER/NIPLER HOMOKINETISKE LED DIFFERENTIALESIDE

Kapacitet: 160 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

SMØREPUNKTER/NIPLER HOMOKINETISKE LED HJULSIDE

Kapacitet: 282 gram

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

ALFA ROMEO (EU) 159 939 159 2.0 JTDM 16V (125 KW) (2009-2011)

**KØLESYSTEM**

Kapacitet: 6,1 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF*Kontroller alle 24 måneder/ 30000 km***KLIMAANLÆGSKOMPRESSOR**Kapacitet: 130 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.