

ALFA ROMEO (EU) 159 939 159 2.2 JTS (2005-2010)



MOTOR 939A5000
Kapacitet: 5,4 liter

ANVEND		KLIMA
Fleksibel (max)		Moderat
PRODUKTANBEFALING 1		
Emperol 5W-40		

Kontroller alle 3000 km, skift alle 30000 km/ 24 måneder

TRANSAKSEL MANUEL 6/1

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Gear 5015		

GEARAGGREGAT Selespeed
Kapacitet: 0,7 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3023		

Kontroller alle 30000 km

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Skift alle 30000 km/ 24 måneder

SERVOSTYRING

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		

Kontroller alle 24 måneder/ 30000 km

SMØREPUNKTER/NIPLER HOMOKINETISKE LED DIFFERENTIALESIDE
Kapacitet: 140 gram

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

ALFA ROMEO (EU) 159 939 159 2.2 JTS (2005-2010)



SMØREPUNKTER/NIPLER HOMOKINETISKE LED HJULSIDE

Kapacitet: 203 gram

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

MoS2 Grease EP 2

KØLESYSTEM

Kapacitet: 8,15 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

Coolant SP 15+

PRODUKTANBEFALING 2

Coolant SP 12

PRODUKTANBEFALING 3

Coolant -38 Organic NF

Kontroller alle 24 måneder/ 30000 km

KLIMAANLÆGSKOMPRESSOR

Kapacitet: 130 cm³

Vi kan desværre ikke give en standardanbefaling til denne komponent. Kontakt venligst vores serviceafdeling.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.