

ALFA ROMEO (EU) 164 164 164 3.0 V6 SUPER (1992-1998)



MOTOR 64305

Kapacitet: 7,8 liter (Førstegangsupfyldning), Kapacitet: 7,5 liter (Servicepåfyldning)

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Emperol Racing 10W-60	Emperol 10W-40

Kontroller alle 500 km, skift alle 20000 km/ 12 måneder

ANVEND	KLIMA
Normal	Arktisk

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
Duranza LSP 5W-30	Asyntho 5W-30

Kontroller alle 500 km, skift alle 20000 km/ 12 måneder

TRANSAKSEL AUTOMATISK 043 4/1

Kapacitet: 4,2 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
ATF Dexron II-D	

Kontroller alle 20000 km, skift alle 40000 km

TRANSAKSEL AUTOMATISK 060 4/1

Kapacitet: 4,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	
ATF Dexron II-D	

Kontroller alle 20000 km, skift alle 40000 km

TRANSAKSEL MANUEL 5/1

Kapacitet: 1,8 liter

ANVEND	KLIMA
Normal	Moderat

PRODUKTANBEFALING 1	PRODUKTANBEFALING 2
SP Gear 5015	Gearlube GL-4 80W

Kontroller alle 40000 km, skift alle 120000 km

ALFA ROMEO (EU) 164 164 164 3.0 V6 SUPER (1992-1998)



HYDRAULISK BREMSE- & KOBLINGSSYSTEM

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Kontroller alle 500 km, skift alle 12 måneder

SERVOSTYRING

Kapacitet: 0,9 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
ATF Dexron II-D		

Kontroller alle 500 km

KØLESYSTEM

Kapacitet: 12 liter (Førstegangsupfyldning), Kapacitet: 9,5 liter (Servicepåfyldning)

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
Coolant -38 Organic NF		

Kontroller alle 500 km, skift alle 60000 km/ 24 måneder

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.