

# ALFA ROMEO (EU) GIULIETTA 940

## GIULIETTA 2.0 JTDM (103 KW) (2015-2018)



### MOTOR 940C3000

Kapacitet: 4,2 liter (Servicepåfyldning)

| ANVEND                  | KLIMA   |
|-------------------------|---------|
| Svær, fleksibel (maks.) | Moderat |

PRODUKTANBEFALING 1

**Avanza MSP 0W-30**

Skift alle 12 måneder

| ANVEND          | KLIMA   |
|-----------------|---------|
| Fleksibel (max) | Moderat |

PRODUKTANBEFALING 1

**Avanza MSP 0W-30**

Skift alle 35000 km/ 24 måneder

### TRANSAKSEL MANUEL 6/1

Kapacitet: 2 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**SP Gear 1081**

PRODUKTANBEFALING 2

**SP Gear 5015**

Kontroller alle 35000 km

### HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

Kapacitet: 0,8 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Skift alle 35000 km/ 24 måneder

### KØLESYSTEM

Kapacitet: 6,7 liter

| ANVEND | KLIMA   |
|--------|---------|
| Normal | Moderat |

PRODUKTANBEFALING 1

**Coolant SP 14+**

Kontroller alle 35000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.