

# ALFA ROMEO (EU) SPIDER 115 ALFA SPIDER 2.0 QUADRIFOGLIO VERDE (1990-1993)



## MOTOR

Kapacitet: 6,6 liter, Filterkapacitet: 0,5 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Emperol 10W-40**

Kontroller alle 500 km, skift alle 20000 km/ 12 måneder

## DIFFERENTIALE BAG (4x2)

Kapacitet: 1,4 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

## GEAR MANUEL 5/1

Kapacitet: 1,85 liter

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

Kontroller alle 20000 km, skift alle 40000 km/ 24 måneder

## HYDRAULISK BREMSE- & KOBLINGSSYSTEM

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**Drauliquid-LV Super DOT 4**

### PRODUKTANBEFALING 2

**Drauliquid-S DOT 4**

Kontroller alle 500 km, skift alle 12 måneder

## SERVOSTYRING

### ANVEND

Normal

### KLIMA

Moderat

### PRODUKTANBEFALING 1

**ATF Dexron II-D**

Kontroller alle 500 km

# ALFA ROMEO (EU) SPIDER 115 ALFA SPIDER 2.0 QUADRIFOGLIO VERDE (1990-1993)



## SMØREPUNKTER/NIPLER KARDANAKSLENS GLIDESAMLINGER

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gear Grease EP 1**

*Kontroller alle 20000 km/ 12 måneder*

## KØLESYSTEM

Kapacitet: 8,5 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Coolant -38 Organic NF**

*Kontroller alle 500 km, skift alle 60000 km/ 24 måneder*

## STYREHUS

Kapacitet: 0,14 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

**Gearlube GL-5 80W-90**

*Kontroller alle 20000 km/ 12 måneder*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.