

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4 (2008-2010)



MOTOR 939A000
Kapacitet: 5,4 liter

ANVEND

Fleksibel (max)

KLIMA

Moderat

PRODUKTANBEFALING 1

Emperol 5W-40

Skift alle 35000 km

DIFFERENTIALE BAG

Kapacitet: 0,75 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Syngear 75W-90

Skift alle 140000 km

REDUKTIONSGEARKASSE

Kapacitet: 0,6 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 1071

PRODUKTANBEFALING 2

Syngear 75W-90

Skift alle 140000 km

TRANSAKSEL AUTOMATISK Aisin Warner AF 40-6 6/1

Kapacitet: 3,3 liter (Servicepåfyldning), Kapacitet: 6,1 liter (Tør efterfyld)

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Matic 4026

Kontroller alle 35000 km

TRANSAKSEL MANUEL 6/1

Kapacitet: 2,8 liter

ANVEND

Normal

KLIMA

Moderat

PRODUKTANBEFALING 1

SP Gear 5015

Kontroller alle 35000 km

ALFA ROMEO (EU) SPIDER 939 SPIDER 3.2 JTS V6 Q4 (2008-2010)



HYDRAULISK SYSTEM (TAG) ELEKTRONISK/HYDRAULISK

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		
<i>Kontroller alle 35000 km</i>		

HYDRAULISK BREMSE-/KOPLINGSSYSTEM ABS

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	
<i>Skift alle 35000 km/ 24 måneder</i>		

SERVOSTYRING

Kapacitet: 1,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1		
SP Fluid 3013		
<i>Kontroller alle 35000 km</i>		

KØLESYSTEM

Kapacitet: 10,3 liter

ANVEND		KLIMA
Normal		Moderat
PRODUKTANBEFALING 1	PRODUKTANBEFALING 2	PRODUKTANBEFALING 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF
<i>Kontroller alle 35000 km</i>		

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.