

ALFA ROMEO (EU) 145 930 145 JTD (1999-2000)



ENGINE AR 32302
Capacity: 4,4 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Emperol 10W-40

Check every 1000 km, change every 10000 km/ 18 months

USE	CLIMATE
Normal	Arctic

PRODUCT RECOMMENDATION 1

Emperol 5W-40

PRODUCT RECOMMENDATION 2

Asyntho 5W-30

Check every 1000 km, change every 10000 km/ 18 months

TRANSAXLE MANUAL 5/1
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

PRODUCT RECOMMENDATION 2

SP Gear 1071

Check every 80000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Check every 1000 km, change every 60000 km/ 24 months

POWER STEERING
Capacity: 1,3 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D

Check every 1000 km

ALFA ROMEO (EU) 145 930 145 JTD (1999-2000)

**COOLING SYSTEM**

Capacity: 6,1 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

Coolant -38 Organic NF*Check every 1000 km*

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.