

ALFA ROMEO (EU) 159 939 159 2.4 JTDM 20V (2005-2007)



ENGINE 939A3000
Capacity: 6,4 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Check every 3000 km, change every 30000 km/ 24 months

TRANSAXLE AUTOMATIC Aisin Warner AF 40-6 6/1
Capacity: 6,1 liter (Dry fill), Capacity: 3,3 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 30000 km

TRANSAXLE MANUAL 6/1
Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 30000 km/ 24 months

POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 24 months/ 30000 km

ALFA ROMEO (EU) 159 939 159 2.4 JTDM 20V (2005-2007)



GREASE POINTS/NIPPLES HOMOKINETIC JOINTS DIFFERENTIAL SIDE

Capacity: 160 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

GREASE POINTS/NIPPLES HOMOKINETIC JOINTS WHEEL SIDE

Capacity: 282 grams

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
MoS2 Grease EP 2		

COOLING SYSTEM

Capacity: 7,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 24 months/ 30000 km

AIRCONDITIONING COMPRESSOR

Capacity: 130 CM3

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.