ALFA ROMEO (EU) 164 164 164 3.0 V6 24V QV (1992-1993)



	CLIMATE
	Moderate
PRODUCT RECOMMENDATION 2	
Emperol 10W-40	
km/ 12 months	
	CLIMATE
	Arctic
PRODUCT RECOMMENDATION 2	
Asyntho 5W-30	
	Emperol 10W-40 km/ 12 months PRODUCT RECOMMENDATION 2

TRANSAXLE MANUAL 5/1 Capacity: 1,8 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 5015	Gearlube GL-4 80W	
Check every 40000 km, change ev	ery 120000 km	<u> </u>

HYDRAULIC BRAKE/CLUTCH SYSTEM		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Check every 500 km, change every 12 months

Check every 500 km, change every 10000 km/ 12 months

POWER STEERING Capacity: 0,9 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
ATF Dexron II-D	
Check every 500 km	

PRODUCT RECOMMENDATION

ALFA ROMEO (EU) 164 164 164 3.0 V6 24V **QV** (1992-1993)



COOLING SYSTEM Capacity: 9,5 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant -38 Organic NF	
Check every 500 km, change every 60000 km/ 24 mon	iths

Check every 500 km, change every 60000 km/ 24 months

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.