

ALFA ROMEO (EU) BRERA 939 BRERA 2.4 JTDM 20V (147 KW) (2008-2010)



ENGINE 939A3000
Capacity: 6,4 liter

USE

Flexible (max)

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol 5W-40

Change every 35000 km

TRANSAXLE AUTOMATIC Aisin Warner AF 40-6 6/1
Capacity: 6,1 liter (Dry fill), Capacity: 3,3 liter (Service fill)

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Matic 4026

Check every 35000 km

TRANSAXLE MANUAL 6/1
Capacity: 2,8 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 5015

Check every 35000 km

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4

Change every 35000 km/ 24 months

POWER STEERING

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3013

Check every 35000 km

ALFA ROMEO (EU) BRERA 939 BRERA 2.4 JTDM 20V (147 KW) (2008-2010)

**COOLING SYSTEM**

Capacity: 7,35 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 35000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.