ALFA ROMEO (EU) GIULIETTA 940 GIULIETTA 1.4 TURBO BIFUEL (88 KW)



(2011-2021)

ENGINE 198A4000 / 940B7000 LPG Capacity: 3,1 liter (Service fill)				
USE		CLIMATE		
Severe, flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1				
Specialsynth MSP 5W-40				
Check every 3000 km, change every 10000 km/ 12 months				
USE		CLIMATE		
Flexible (max)		Moderate		
PRODUCT RECOMMENDATION 1				
Specialsynth MSP 5W-40				
Change every 30000 km/ 24 months				

TRANSAXLE MANUAL 6/1 Capacity: 2 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
SP Gear 1081	SP Gear 5015	
Check every 30000 km	'	,

HYDRAULIC BRAKE/CLUTCH SYSTEM ABS Capacity: 0,8 liter				
USE		CLIMATE		
Normal		Moderate		
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2			
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4			
Change every 24 months				

COOLING SYSTEM Capacity: 5,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Coolant SP 14+	
Check every 30000 km	·

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.