

ALFA ROMEO (EU) GIULIETTA 940

GIULIETTA 2.0 JTDM (129 KW) (2013-2018)



ENGINE 940B4000
Capacity: 4,2-4,8 liter (Service fill)

USE	CLIMATE
Severe, flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30*Change every 12 months*

USE	CLIMATE
Flexible (max)	Moderate

PRODUCT RECOMMENDATION 1

Avanza MSP 0W-30*Change every 35000 km/ 24 months*

TRANSAXLE MANUAL 6/1
Capacity: 2 liter

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015*Check every 35000 km*

TRANSAXLE SEMI-AUTOMATIC C635 DDCT 6/1

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1081

PRODUCT RECOMMENDATION 2

SP Gear 5015*Check every 30000 km*

HYDRAULIC ACTUATION GEARBOX

USE	CLIMATE
Normal	Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023*Check every 30000 km*

ALFA ROMEO (EU) GIULIETTA 940

GIULIETTA 2.0 JTDM (129 KW) (2013-2018)



HYDRAULIC BRAKE/CLUTCH SYSTEM ABS

Capacity: 0,8 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
Drauliquid-LV Super DOT 4	Drauliquid-S DOT 4	

Change every 35000 km/ 24 months

COOLING SYSTEM

Capacity: 6,7 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1		
Coolant SP 14+		

Check every 35000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.