

ALFA ROMEO (EU) GT 937 GT 2.0 JTS (119 KW) (2004-2011)

**ENGINE 932A2000**

Capacity: 4,4 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Emperol Racing 10W-60*Change every 20000 km***TRANSAXLE MANUAL 5/1**

Capacity: 2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Gear 1071

PRODUCT RECOMMENDATION 2

Syngear 75W-90*Check every 80000 km***GEAR OPERATING SYSTEM Selespeed**

Capacity: 0,6 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

SP Fluid 3023*Check every 20000 km***HYDRAULIC BRAKE/CLUTCH SYSTEM ABS**

Capacity: 0,52 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

Drauliquid-LV Super DOT 4

PRODUCT RECOMMENDATION 2

Drauliquid-S DOT 4*Check every 20000 km, change every 60000 km/ 24 months***POWER STEERING**

Capacity: 1,2 liter

USE

Normal

CLIMATE

Moderate

PRODUCT RECOMMENDATION 1

ATF Dexron II-D*Check every 20000 km*

ALFA ROMEO (EU) GT 937 GT 2.0 JTS (119 KW) (2004-2011)



COOLING SYSTEM

Capacity: 7,2 liter

USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 20000 km

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.