## **ASTON MARTIN DB9 DB9** (2003-2008)



ENGINE Capacity: 10 liter, Filter capacity: 1 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Helar 0W-40	

Change every 16000 km/ 12 months

DIFFERENTIAL FROM AUTOMAT Capacity: 1,6 liter	IC	
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
SP Gear 1011	Syngear TDL 75W-90	Syngear 75W-90
Change every 32000 km/ 24 month	S	

TRANSAXLE MANUAL Graziano 6/1
Capacity: 5 liter

USE

Normal

PRODUCT RECOMMENDATION 1

SP Gear 1011

CLIMATE

Moderate

PRODUCT RECOMMENDATION 2

PRODUCT RECOMMENDATION 3

Syngear TDL 75W-90

Syngear 75W-90

Check every 32000 km/36 months, change every 64000 km/48 months

TRANSMISSION AUTOMATIC ZF 6HP26 6/1 Capacity: 9,7 liter	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
SP Matic 4026	
Check every 16000 km/ 12 months	·

HYDRAULIC BRAKE/CLUTCH SYSTEM	
USE	CLIMATE
Normal	Moderate
PRODUCT RECOMMENDATION 1	
Drauliquid-S DOT 4	
Check every 16000 km, change every 12 months	·

## **ASTON MARTIN DB9 DB9** (2003-2008)



POWER STEERING Capacity: 1,3 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	
ATF Almirol	SP Fluid 3013	
Check every 16000 km/ 12 months	•	,

COOLING SYSTEM Capacity: 15 liter		
USE		CLIMATE
Normal		Moderate
PRODUCT RECOMMENDATION 1	PRODUCT RECOMMENDATION 2	PRODUCT RECOMMENDATION 3
Coolant SP 15+	Coolant SP 12	Coolant -38 Organic NF

Check every 16000 km/ 12 months, change every 160000 km/ 60 months

## **AIRCONDITIONING** Capacity: 750 grams

We are unable to give a standard recommendation for this component. Please contact our service department.

The data mentioned in this product information sheet is meant to enable the reader to orientate himself about the properties and possible applications of our products. Although this overview is composed with all possible care on the stated date, the compiler does not accept any liability for damages caused by incompleteness and/or inaccuracies in this information, especially when these are caused by obvious typing errors. The terms of delivery of the supplier apply to all product supplies. The reader is advised, especially for critical applications, to make the final product choice in consultation with the supplier. Due to continual product research and development, the information contained herein is subject to changes without notification.